



LINGJACK

林傑

20KG CO2 STORED PRESSURE MOBILE FIRE EXTINGUISHER

MODEL : C-20C

Specification :

- Capacity : 20 kg
- Extinguishing Medium : CO2
- Propellant Type : CO2
- Discharge Time : 44 secs
- Discharge Range : 10 m
- Working Pressure : 60 bar @ 20°C
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 3/8" x 6 meters
(Optional Up To 12 meter Upon Request)
- Wheel Size : Diameter 406mm x 50mm
- Size : 590 (L) x 640 (D) x 1470(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 90 kg



Features :

- Heavy Duty Hose
- Forged Brass Chrome Plated Operating Valve with In-Built Safety Relief
- Suitable to Use on Live Electrical Equipment Up to 1000V
- Suitable for Electrical Fire
- Solid Rubber Wheel for Easy Maneuverable


Standards : Manufactured In Accordance With BS EN 1866-1 : 2007

Approvals : LPCB (UK), SETSCO (SG), BUREAU VERITAS (BV)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	Class Of Fire	Standard	Approval
20802329	89B	B	BS EN 1866-1:2007	LPCB
2080232900001	89B	B	BS EN 1866-1:2007	SETSCO
20805750	89B	B	BS EN 1866-1:2007	BV (MED)



GOOD QUALITY GREAT SERVICES

www.lingjack.com