



LINGJACK

林傑

2KG CO2 STORED PRESSURE FIRE EXTINGUISHER

MODEL : C-2CSEC

Specification :

- Capacity : 2 kg
- Extinguishing Medium : CO2
- Propellant Type : CO2
- Discharge Time : 9.8 sec
- Discharge Range : 2 m
- Working Pressure : 60 bar
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 440 mm
- Size : Dia. 114 x 500(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 7.5 kg



Features :

- Heavy Duty Hose
- Effective Suppression of Class B Fires
- Suitable to Use on Live Electrical Equipment Up to 1000V (Only Applicable To LPCB Approval Model)
- High Pressure Hardware

Standards : Manufactured In Accordance With EN 3-7

Approvals : LPCB (UK),SETSCO (SG)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20800613	34B	B	BS EN 3-7:2004+A1:2007	LPCB
20800600	34B	B	SS EN 3-7 : 2012	SETSCO



EN3-7:2004 + A1:2007
Cert No. 501a



GOOD QUALITY GREAT SERVICES

www.lingjack.com