



LINGJACK

林傑

3/4"x30m SWING HOSEREEL

Specification : HR-19AS

- Hose Size : 3/4 " x 30m
- Design Pressure : 12 bar
- Working Temperature : 5 Deg C to 55 Deg C
- Hydrostatic Test Pressure : 18 bar at 5 mins
- Nozzle : 3/4 " Nickel Plated Chrome Brass Jet Nozzle
- Flow Rate (Jet Nozzle) : 41.2 lpm at 6 bar
- K-Factor : 16.82
- Material : Electro Galvanized Plate
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 20.0 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated Hose Reel
- High Quality Red Semi-Rigid Fire Hose Approved to EN694:2014
- Easy to Maneuver
- Easily Mountable Universal Swing Armset



Standards : Manufactured in accordance with EN 671-1:2012

Approvals : LPCB (UK)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Model	Type	Inlet Connection	Overall Size	Approval
80800504	HR-19AS	Automatic	1" BSP(F) Thread	Overall Size : Dia.: 525 x 245 (±5) (Depth)	LPCB
80800300	HR-3/4SW	Manual	3/4" BSPT(M) Thread	Overall Size : Dia.: 525 x 270 (±5) (Depth)	-



EN 671 – 1: 2012
Cert No. 501b

GOOD QUALITY GREAT SERVICES

www.lingjack.com