



LINGJACK

林傑

6LTR WET CHEMICAL STORED PRESSURE FIRE EXTINGUISHER

MODEL : C-6KSE (F6)

Specification :

- Capacity : 6 ltr
- Extinguishing Medium : PREMIX (50% Water+50% Fatseal)
- Propellant Type : Nitrogen
- Discharge Time : 77 sec
- Discharge Range : 7 m
- Working Pressure : 9 bar (± 3 bar within green zone)
- Working Temperature : 0Deg C to +60 Deg C
- Hose Length : 295 mm
- Size : Dia. 160 x 514(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 13.36 kg

Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Effective Suppression of Class A, B & F Fires

Standards : Manufactured In Accordance With EN 3-7

Approvals : SETSCO (SG)

Origin : Made in Singapore



Ordering Matrix :

Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20803505	21A, 113B, 75F	A, B, F	BS EN 3-7:2004+A1:2007	-

GOOD QUALITY GREAT SERVICES

www.lingjack.com

Specification subjects to change without prior notice (0721 R02)