

A high-speed photograph of a water droplet hitting a surface, creating a splash with several smaller droplets and ripples. The entire image is framed by a thick, irregular red border.


Mueller Co.

Pioneer and Leader in potable
water distribution solutions
and fire protection

Our long history confirms our industry leadership

**Established 1857 by
Hieronymus Mueller
in Decatur, IL**

**Among first members
of American Water
Works Association**



Mueller Water Products

A Smart *Move*™ for delivering safe, clean drinking water

The logo for Mueller Co. features the company name in a bold, black, sans-serif font, enclosed within a red rectangular border with rounded corners. The logo is set against a light gray background and is reflected below it.

During the past 150 years, Mueller Co. has become synonymous with the innovation that has enabled utilities to accurately measure and regulate the flow of water as it is transmitted from source to customer. It has developed many 'industry firsts' in the water infrastructure space that have become industry standards.

For more than 150 years, the companies that make up Mueller Water Products have provided products and services recognized for quality, dependability and innovation.

NYSE: MWA



For more than 150 years, Anvil has worked diligently to build a strong, vibrant tradition of making connections — from pipe to pipe and people to people. We provide expertise and product solutions for a wide range of applications, from plumbing and mechanical, HVAC, industrial and fire protection to mining, and oil and gas.



MUELLER® INTERNATIONAL DIVISION

About Us

Since 1857, the Mueller name has been associated with dependable water and gas distribution products around the globe. With a foundation of solid core values and a clear mission, Mueller's International Division is the sales and marketing arm outside of North America for nearly all of the company's brands and affiliates. This includes:

Mueller®

US Pipe® Valve & Hydrant

Jones®

Hydro-Guard®

Henry Pratt®

Milliken Valve™

Hydro Gate®


Lined Valve™

Mueller Systems™

Echologics®

Mueller Gas





Mueller products meet or exceed industry standards

ASSE **ANSI**

AWWA

ULC

ISO

API



ASME

CFM

DOT




Mueller Co.

Mueller Co.

Resilient Wedge Gate valves and Post Indicators

UL Listed
and
FM Approved



Mueller Co

Industrial Fire Protection

Resilient Wedge Gate Valves

- Non-Rising Stem (NRS) Model : A-2361
 - 4" – 12" | 350 PSI
 - 14" – 16" | 250 PSI
 - 18" – 24" | 175 PSI
- Outside Screw & Yoke (OS&Y) Model : R-2361
 - 2" | 200 PSI
 - 2.5" – 3" | 250 PSI
 - 4" – 12" | 350 PSI
- Post Indicator Valves (PIV) Model : P-2361
 - 4" – 12" | 350 PSI
 - 14" – 16" | 250 PSI
 - 18" – 24" | 175 PSI

Swing Check Valves Model : A2120 or A2122

- 2½" – 12" | 200 PSI



Mueller Co

Industrial Fire Protection (Cont'd)

Indicator Posts

- Non-Adjustable
 - 4" – 14" | Model: A-20808
 - 16" – 24" | Model: A-20809
- Adjustable
 - 4" – 14" | Model: A-20806
 - 16" – 24" | Model: A-20807
- Short Bury
 - 4" – 14" | Model: A-20806S
 - 16" – 24" | Model: A-20807S
- Wall Type
 - 4" – 14" | Model: A-20814



Mueller Co.

Mueller Co.

Hydrants

Almost half of all sold
in North America are
Centurion® brand

Dry Barrel



Mueller Co

Industrial Fire Protection (Cont'd)

Fire Hydrants (Wet Barrel)

- 3 Nozzle (Ductile Iron) | Model: M4060
 - Pumper Nozzle available in 4" or 4½"
 - Hose Nozzles available in 2½"
- 2 Nozzle (Cast Iron) | Model: M4040
 - 4" Pumper & 2½" Hose Nozzles
- Monitor 3-Way (Ductile Iron) | Model: M4060M
 - Pumper Nozzle available in 4" or 4½"
 - Hose Nozzles available in 2½"
- Break Check Valve | Model: M5000 series
 - Available with 6 or 8 holes inlet/adaptor plate



Mueller Co

Industrial Fire Protection (Cont'd)

Fire Hydrants (Dry Barrel)

- 2-Way (Cast Iron) | 200 PSI Model: A435
 - Available in 5¼" or 4½" Main Valve Opening
 - 6" Flanged Shoe
 - 4" Pumper & 2½" Hose Nozzles
- 3-Way Super Centurion (Cast Iron) | 250 PSI Model: A423
 - Available in 5¼" or 4½" Main Valve Opening
 - 6" Flanged Shoe
 - 4½" Pumper and 2½" Hose Nozzles
- 3-Way Super Centurion Monitor (Cast Iron) | Model: A479
 - Pumper Nozzle available in 4" or 4½"
 - Hose Nozzles available in 2½"



Mueller Co

Industrial Fire Protection (Cont'd)

Fire Hydrants (Dry Barrel)

- 4-Way Super Centurion (Cast Iron) | 250 PSI
 - Model A-459 | 5¼" Main Valve Opening | 2-Pumper & 2-Hose Nozzles
 - Model A-458 | 5¼" Main Valve Opening | 1-Pumper & 3-Hose Nozzles
 - Model A-454 | 5¼" Main Valve Opening | 3-Hose Nozzles
 - Model A-455 | 4½" Main Valve Opening | 4-Hose Nozzles
- Flush Type (Cast Iron) | 150 PSI Model: A415
 - Model A-415 | 5¼" Main Valve Opening | 1-Pumper & 2-Hose Nozzles
 - Model A-412 | 2 1/8" Main Valve Opening | 1-Hose Nozzles



A-415 (A-24042)
Standard Flush Fire Hydrant



Hydrants

Wet Barrel




James Jones Industrial Fire Protection



Fire Hydrants (Wet Barrel)

- 3 Nozzle (Ductile Iron) | Model: J4060
 - Pumper Nozzle available in 4" or 4½"
 - Hose Nozzles available in 2½"
- 2 Nozzle (Cast Iron) | Model: J4040
 - 4" Pumper & 2½" Hose Nozzles
- Monitor 3-Way (Ductile Iron) | Model: J4060M
 - Pumper Nozzle available in 4" or 4½"
 - Hose Nozzles available in 2½"
- Break Check Valve | Model: J5000 series
 - Available with 6 or 8 holes inlet/adaptor plate
- 2 Nozzle Platform (Bronze) | Model: J6200
 - 2½" x 2½" Nozzle Configuration





**VALVE &
HYDRANT
DIVISION**

Similar Range of Fire Protection Products



US Pipe Valve & Hydrant Industrial Fire Protection



**VALVE &
HYDRANT
DIVISION**

Resilient Wedge Gate Valves

- Non-Rising Stem (NRS) Model : A-USP1
 - 4" – 12" | 350 PSI
 - 14" – 16" | 250 PSI
 - 18" – 24" | 175 PSI
- Outside Screw & Yoke (OS&Y) Model : R-USP1
 - 2" | 200 PSI
 - 2.5" – 3" | 250 PSI
 - 4" – 12" | 350 PSI
- Post Indicator Valves (PIV) Model : P-USP1
 - 4" – 12" | 350 PSI
 - 14" – 16" | 250 PSI
 - 18" – 24" | 175 PSI

Swing Check Valves Model : U2120 or U2122

- 2½" – 12" | 200 PSI



US Pipe Valve & Hydrant Industrial Fire Protection



**VALVE &
HYDRANT
DIVISION**

Indicator Posts

- Non-Adjustable
 - 4" – 14" | Model: U-20808
 - 16" – 24" | Model: U-20809
- Adjustable
 - 4" – 14" | Model: U-20806
 - 16" – 24" | Model: U-20807
- Wall Type
 - 4" – 14" | Model: U-20814



US Pipe Valve & Hydrant Industrial Fire Protection



**VALVE &
HYDRANT
DIVISION**

Fire Hydrants (Dry Barrel)

- 3-Way Sentinel (Ductile Iron) | 250 PSI
 - Available in 5¼" (model: A-453) or 4½" (A-451) Main Valve Opening
 - 6" Flanged Shoe
 - 4½" Pumper and 2½" Hose Nozzles



Mueller Co.

PRATT
Henry Pratt Company

Fire Protection Products



Henry Pratt Industrial Fire Protection



Post Indicator Valve Assembly (PIVA)

- Quarter Turn Butterfly Type
 - 4" – 24" | 250 PSI (UL Listed) | 175 PSI (FM Approved)
 - Post and Valve assembly tested together
 - Available in Wafer or Flange

Indicating Butterfly Valve (IBV)

- 4" – 24" | 250 PSI (UL Listed)
- Available in Flanged connection

Ground Hog Butterfly Valves

- 4" – 12" | 175 PSI (UL Listed)
- 14" – 24" | 150 PSI (UL Listed)
- Available in Flanged connection



Thank You

