



LINGJACK

林傑

2 ½" OBLIQUE LANDING VALVE

Specification :

- Inlet : 2 ½" PN16 Flange
(Optional Inlet Size And Type Upon Request)
- Outlet : 2 ½" BS336 Female Instantaneous
(Optional Outlet Connection Upon Request)
- Design Pressure : 15 bar
- Seat Test Pressure : 16.5 bar
- Body Test Pressure : 22.5 bar
- Working Temperature : 0°C - 38°C
- Friction Loss : 0.7 bar
- Flow Rate : 9 L/sec at 4.7 bar ± 3 %
- K-Factor : 249.08
- Finishing : Red
(Optional Yellow Color Upon Request)
- Cast/Ductile Iron Hand Wheel Size : Ø150mm x 15mm (Thk)
(Optional Material Upon Request)
- Body Material : Gunmetal LG2
- Accessories : Plastic Blank Cap with SS Chain
(Optional Material Upon Request)
- Gross Weight : Approximate 7.5 kg (Flange Type),
Approximate 5.5 kg (Screw Type)



Features :

- Low Maintenance
- Excellence Quality
- High Flow Rate

Standards : Manufactured in accordance with BS5041-1 : 1987

Approvals : LPCB (UK) , SETSCO (SG)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Inlet Connection	Color	Model	Approval
03104400	2 ½" PN16 FF Flange	Red	LV-OF25	LPCB
03036205	2 ½" ANSI#150 FF Flange	Red	LV-OF25	LPCB
03033801	2 ½" BSPT(M) Thread	Red	LV-DR25	LPCB
90800500	2 ½" BSPT(M) Thread	Yellow	LV-DR25	SETSCO
90800509	2 ½" BSPT(M) Thread	Red	LV-DR25	SETSCO
90800513	2 ½" BSPT(M) Thread	Yellow	LV-DR25	SETSCO cw Steel Rope



www.lingjack.com