



# LINGJACK

## 林傑

### 2 ½" Gate VALVE

#### Specification :

- Inlet : 2 ½" PN16 Flange  
(Optional Inlet Size And Type Upon Request)
- Outlet : 2 ½" BS336 Female Instantaneous
- Design Pressure : 15 bar
- Seat Test Pressure : 16.5 bar
- Body Test Pressure : 22.5 bar
- Friction Loss : 0.7 bar
- Flow Rate : 9 L/sec at 4.7 bar ± 3%
- K-Factor : 249.08
- Finishing : Bare  
(Optional Color Upon Request)
- Cast Iron Hand Wheel Size : Ø135mm x 15mm (Thk)  
(Optional Material Upon Request)
- Body Material : Gunmetal LG2
- Accessories : Plastic Blank Cap with SS Chain  
(Optional Material Upon Request)
- Gross Weight : Approximate 9.3 kg (Flange Type)  
Approximate 6.6kg (Screw Type)



#### Features :

- Low Maintenance
- Excellence Quality
- High Flow Rate

**Standards :** Manufactured in accordance with BS5041-1 : 1987

**Origin :** Made in Singapore

#### Ordering Matrix :

Com No.	Inlet Connection	Model
03034401	2 ½" PN16 FF Flange	GV-FP25
03034701	2 ½" BSPT(M) Thread	GV-SM25
03075701	2 ½" BSPT(F) Thread	GV-SF25

**GOOD QUALITY GREAT SERVICES**

[www.lingjack.com](http://www.lingjack.com)