



LINGJACK

林傑

11KG MONNEX CARTRIDGE OPERATED FIRE EXTINGUISHER MODEL : C-11MCE

Specification :

- Capacity : 11 kg
- Extinguishing Medium : Monnex BC Powder
- Propellant Type : 225 gram CO₂
- Discharge Time : 28 sec
- Discharge Range : 7 m
- Working Pressure : 14 Bar @ 20 Deg C
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 620 mm
- Size : Dia. 181 x 654(H) mm
- Finishing : Red Color
- Gross Weight : Approximate 17.8 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Effective Suppression of Class B Fires
- Effective Suppression of Class C Fires
(Only Applicable To BS EN 3-7 Model)
- Suitable to Use on Live Electrical Equipment Up to 1000V
(Only Applicable To BS EN 3-7 Model)

Standards : Manufactured In Accordance With EN 3-7

Approvals : LPCB (UK)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20808901	233B	B, C	BS EN 3-7:2004+A1:2007	LPCB



EN3-7:2004 + A1:2007
Cert No. 501h

GOOD QUALITY GREAT SERVICES

www.lingjack.com

LEW-MDS-C11MSE Rev02 (Nov24)
Specification subjects to change without prior notice