



LINGJACK

林傑

5KG CO2 STORED PRESSURE FIRE EXTINGUISHER

MODEL : C-5CSEC

Specification :

- Capacity : 5 kg
- Extinguishing Medium : CO2
- Propellant Type : CO2
- Discharge Time : 13 sec
- Discharge Range : 2 m
- Working Pressure : 60 bar
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 440 mm
- Size : Dia. 155 x 645(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 17.0 kg

Features :

- Heavy Duty Hose
- Effective Suppression of Class B Fires
- Suitable to Use on Live Electrical Equipment Up to 1000V
(Only Applicable To LPCB Approval Model)
- High Pressure Hardware




Standards : Manufactured In Accordance With EN 3-7

Approvals : LPCB (UK), SETSCO (SG)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20800713	55B	B	BS EN 3-7:2004+A1:2007	LPCB
20800700	55B	B	SS EN 3-7 : 2012	SETSCO
2080071300003	55B	B	BS EN 3-7:2004+A1:2007	BV (MED)



GOOD QUALITY GREAT SERVICES

www.lingjack.com

LEW-MDS-C5CSEC Rev00 (Dec21)
Specification subjects to change without prior notice