



# LINGJACK

## 林傑

### 6KG ABC STORED PRESSURE FIRE EXTINGUISHER

**MODEL : C-6ASE**

#### Specification :

- Capacity : 6 kg
- Extinguishing Medium : 40% ABC Dry Chemical Powder
- Propellant Type : Nitrogen
- Discharge Time : 19.37 sec
- Discharge Range : 5 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 440 mm
- Size : Dia. 181 x 510(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 9.6 kg

#### Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Effective Suppression of Class A,B Fires
- Effective Suppression of Class C Fires  
(Only Applicable To LPCB Approval Model)
- Suitable to Use on Live Electrical Equipment Up to 1000V  
(Only Applicable To LPCB Approval Model)



**Standards :** Manufactured In Accordance With EN 3-7

**Approvals :** LPCB (UK), SETSCO (SG)

**Origin :** Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20801522	34A, 233B	A, B, C	BS EN 3-7:2004+A1:2007	LPCB
20801502	34A, 233B	A, B	SS EN 3-7 : 2012	SETSCO



**GOOD QUALITY GREAT SERVICES**

[www.lingjack.com](http://www.lingjack.com)

LEW-MDS-C6ASE Rev00 (Dec21)  
Specification subjects to change without prior notice