



LINGJACK

林傑

9LTR FOAM CARTRIDGE OPERATED FIRE EXTINGUISHER

MODEL : C-9FCE

Specification :

- Capacity : 9 ltr
- Extinguishing Medium : Foam
- Propellant Type : 75 gram CO₂
- Discharge Time : 35 sec
- Discharge Range : 7 m
- Working Pressure : 17.0bar
- Working Temperature : +5Deg C to +60 Deg C
- Hose Length : 530 mm
- Size : Dia. 181 x 624(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 13.5 kg

Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Effective Suppression of Class A & B Fires




Standards : Manufactured In Accordance With EN 3-7

Approvals : LPCB (UK)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20801708	34A, 233B	A, B	BS EN 3-7:2004+A1:2007	LPCB
2080170800002	34A, 233B	A, B	BS EN 3-7:2004+A1:2007	BV (MED)



GOOD QUALITY GREAT SERVICES

www.lingjack.com

LEW-MDS-C9FCE Rev00 (Dec21)
Specification subjects to change without prior notice