



LINGJACK

林傑

9LTR WATER ADDITIVES CARTRIDGE OPERATED FIRE EXTINGUISHER MODEL : C-9WCEA

Specification :

- Capacity : 9 ltr
- Extinguishing Medium : Water with Additives
- Propellant Type : 55 gram CO2
- Discharge Time : 71.3 sec
- Discharge Range : 7 m
- Pressure Tmax : 16.5 bar
- Working Temperature : +5Deg C to +60 Deg C
- Hose Length : 540 mm
- Size : Dia. 181 x 624(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 14.7 kg

Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Effective Suppression of Class A Fires

Standards : Manufactured In Accordance With EN 3-7


Approvals : LPCB (UK), BUREAU VERITAS (BV)

Origin : Made in Singapore



Ordering Matrix :

Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20801709	21A	A	BS EN 3-7:2004+A1:2007	LPCB
2080170900001	21A	A	BS EN 3-7:2004+A1:2007	BV (MED)



GOOD QUALITY GREAT SERVICES

www.lingjack.com

LEW-MDS-C9WCEA Rev01 (Nov24)
Specification subjects to change without prior notice