



LINGJACK

林傑

9LTR WATER ADDITIVES STORED PRESSURE FIRE EXTINGUISHER

MODEL : C-9WSEA

Specification :

- Capacity : 9 ltr
- Extinguishing Medium : Water with Additives
- Propellant Type : Nitrogen
- Discharge Time : 49.33 sec
- Discharge Range : 7 m
- Working Pressure : 14 bar
- Working Temperature : +5Deg C to +60 Deg C
- Hose Length : 540 mm
- Size : Dia. 181 x 605(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 13.43 kg

Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Effective Suppression of Class A Fires



Standards : Manufactured In Accordance With EN 3-7

Approvals : LPCB (UK), SETSCO (SG)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20801737	21A	A	BS EN 3-7:2004+A1:2007	LPCB
20804300	21A	A	SS EN 3-7 : 2012	SETSCO



GOOD QUALITY GREAT SERVICES

www.lingjack.com

LEW-MDS-C9WSEA Rev00 (Dec21)
Specification subjects to change without prior notice