



LINGJACK

林傑

150KG PURPLE K CARTRIDGE OPERATED MOBILE FIRE EXTINGUISHER

MODEL : C-150PTC

Specification :

- Capacity : 150 kg
- Extinguishing Medium : Purple K
- Propellant Type : 4.0kg CO2
- Fire Rating : IV B (317B), C
- Class of Fire : B,C
- Discharge Time : 250 secs
- Discharge Range : 10 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 3/4" x 6 meters (Optional Up To 12 meter Upon Request)
- Wheel Size : Diameter 406mm x 50mm
- Size : 650 (L) x 710 (D) x 1320(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 230 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Forged Brass Chrome Plated Operating Valve with In-Build Safety Relief
- Suitable to Use on Live Electrical Equipment Up to 1000V
- Suitable for Electrical Fire
- Solid Rubber Wheel for Easy Maneuverable

Standards : Manufactured In Accordance With BS EN 1866-1 : 2007

Approvals : LPCB (UK), SETSCO (SG)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	Class Of Fire	Standard	Approval
21804600	IVB (317B), C	B, C	BS EN 1866-1:2007	LPCB
2180460000001	IVB (317B)	B	BS EN 1866-1:2007	SETSCO



GOOD QUALITY GREAT SERVICES

www.lingjack.com

LEW-MDS-C150PTC Rev01 (Dec23)
Specification subjects to change without prior notice