



LINGJACK

林傑

50KG ABC CARTRIDGE OPERATED MOBILE FIRE EXTINGUISHER

MODEL : C-50ATC

Specification :

- Capacity : 50 kg
- Extinguishing Medium : ABC 70%
- Propellant Type : 1.5kg CO₂
- Discharge Time : 70 secs
- Discharge Range : 10 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 3/4" x 6 meters
(Optional Up To 12 meter Upon Request)
- Wheel Size : Diameter 406mm x 50mm
- Size : 530 (L) x 550 (D) x 994(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 96 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Forged Brass Chrome Plated Operating Valve with In-Build Safety Relief
- Suitable to Use on Live Electrical Equipment Up to 1000V
- Suitable for Electrical Fire
- Solid Rubber Wheel for Easy Maneuverable


Standards : Manufactured In Accordance With BS EN 1866-1 : 2007

Approvals : LPCB (UK), SETSCO (SG), BUREAU VERITAS (BV)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	Class Of Fire	Standard	Approval
21802700	34A,IVB (317B), C	A, B, C	BS EN 1866-1:2007	LPCB
2180270000001	34A,IVB (317B)	A, B	BS EN 1866-1:2007	SETSCO
2180270000002	34A,IVB (317B), C	A, B, C	BS EN 1866-1:2007	BV (MED)



GOOD QUALITY GREAT SERVICES

www.lingjack.com

LEW-MDS-C50ATC Rev01 (Dec23)

Specification subjects to change without prior notice