



LINGJACK

林傑

1"x30m HIGH PRESSURE HOSEREEL

MODEL : HR-0278, HR-0279, HR-0287

Specification :

- Hose Size : 1" x 30m
- Design Pressure : 20 bar
- Working Temperature : 5 Deg C to 55 Deg C
- Hydrostatic Test Pressure : 30 bar at 5 mins
- Nozzle : C18 Hand Grip Brass Jet Spray Nozzle
- Flow Rate (Jet) : 162 lpm at Inlet 6 bar
- K-Factor : 66.26
- Distance (Jet) : 20m at Inlet 6 bar
- Overall Size : Dia.: 585 x 260 (±5) (Depth)
- Finishing : RAL 3001
- Gross Weight : Approximate 27 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated Hose Reel
- High Quality and Pressure Red Semi Rigid Fire Hose Approved to EN694 : 2014
- 3 Way Control Nozzle (Spray-Jet-Off)
- Gunmetal 180° Double Swing Waterway
- Flexible Mounting Position
- For Offshore Application
- Design Accordance to Norsok Requirement

Standards : Manufactured in accordance with EN 671-1 : 2012

Approvals : LPCB (UK), Wheel Mark (MED)


Origin : Made in Singapore

Ordering Matrix :

Com No.	Model	Waterway Material	Drum Material	Approval
80801300	HR-0278	Gunmetal LG2	Electro Galvanized Plate	LPCB, MED
80801400	HR-0279	Gunmetal LG2	Stainless Steel Plate	LPCB, MED
80801401	HR-0287	Titanium	Stainless Steel Plate	LPCB



EN 671 - 1: 2012
Cert No. 501b



0832

GOOD QUALITY GREAT SERVICES

www.lingjack.com

Specification subjects to change without prior notice (0320R01)