



LINGJACK


林傑

IN-LINE PRESSURE REGULATING VALVE

Model : DF1

Specification :

- Design Pressure : 20 bar
- Seat Test Pressure : 22 bar
- Body Test Pressure : 30 bar
- Working Temperature : 0°C - 38°C
- Operating Inlet Pressure : 5 bar to 20 bar
- K-factor = 93 @ Inlet Pressure 15 bar
- K-factor = 140 @ Inlet Pressure 10 bar
- Flow Rate : 486 Lpm @ 4 bar Drop
- Outlet Running Pressure : 2 bar to 6 bar
(Optional Higher Running Pressure Till 10 bar Upon Request)
- Body Material : Gunmetal LG2
- Hand Wheel Material : Cast Iron
(Optional LG2 Material Upon Request)
- Finishing : Red
- Gross Weight : Approximate 4.3 kg



Features :

- Balance Pressure Control Mechanism
- Could be Manufacture to Flange Inlet and Outlet
(Optional Upon Request)
- Shut Down Feature Design Available

Standards : Manufactured in accordance with EN1074-5

Tested By : SETSCO

Origin : Made in Singapore

Ordering Matrix :

Com No.	Inlet	Outlet	Remark
03186800	2" BSP(F) Thread	2" BSP(F) Thread	W/o Handwheel
03186801	1 1/2" BSP(F) Thread	1 1/2" BSP(F) Thread	W/o Handwheel
03220001	1 1/2" ANSI #150 FF Flange	1 1/2" ANSI #150 FF Flange	Cw Hand Wheel
03220004	2" BSPT(F) Thread	2" BSPT(F) Thread	Cw Hand Wheel

GOOD QUALITY GREAT SERVICES

www.lingjack.com

LEW-MDS-DF1 Rev00 (May24)
Specification subjects to change without prior notice