



PARTS LIST

Item	Description	Material	Com No	Qty
1	SP Turn Valve	Brass HTCZ120317-1	03020004	1
2	23mm Pressure Gauge	-	03000200	1
3	Iron Safety Pin	Nickel Plated Iron	03018600	1
4	25KG Cylinder With 16in Wheel	JIS3141 Cold Roll Sheet 2mm Thick	03067104	1
5	Powder Controllable Discharge Gun	PVC	03079204	1
6	3/4" x 6M Hose Assembly	Rubber	03003303	1
7	Syphon Tube	PVC	03110200	2

Technical Specification

Description	Specification
Extinguisher Medium	ABC Dry Chemical 40% Powder
Working Temperature	-20 To 60DegC
Max. Allowable Pressure, PS	19 Bar
Operating Pressure	14 Bar
Discharge Time	32 Sec
Discharge Effective Range	10 m
Fire Rating	II B (2x21B + 233B = 275B)
Gross Weight	49 Kg

Ordering Matrix

Com No.	Brand	Approval	Remarks
21803100 00000	COMBAT	LPCB	BS EN1866-1
21803100 00004	COMBAT	SETSCO	BS EN1866-1
21803100 00001	COMBAT	BV	MED

LINGJACK ENGINEERING WORKS PTE LTD
 NO.1 WOODLANDS TERRACE #03-01
 LINGJACK INDUSTRIAL BUILDING
 SINGAPORE 738471
 TEL:(65)6759 4163 FAX:(65)6758 7513
 E-MAIL:COMBAT@LINGJACK.COM
 WEBSITE:WWW.COMBAT.COM.SG

Customer : -
 Project : -
 Title : 25Kg Trolley Fire Extinguisher (ABC), Stored Pressure (C-25ATP)
 Drawing No. : 21803100
 Com. No. :
 This drawing contains proprietary information and should not be reproduced or use in any way without written permission from Lingjack Engineering Works Pte Ltd.

Scale : NTS
 Sheet : 1/1
 3rd Angle Projection :

21.1.26	Include ABC 40% Powder.	ZY	Lucas	00	B
17.08.11	Production Drawing.	Fung	Lucas	00	A
Date	Description	Drawn	Approved	GA Rev	Pro Rev