



LINGJACK

林傑

2KG ABC STORED PRESSURE FIRE EXTINGUISHER

MODEL : C-2ASE

Specification :

- Capacity : 2 kg
- Extinguishing Medium : 40% ABC Dry Chemical Powder
- Propellant Type : Nitrogen
- Discharge Time : 9 sec
- Discharge Range : 3 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Size : Dia. 98 x 435(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 3.7 kg

Features :

- Outdoor UV Resistance Polyester Powder Coated
- Durable Plastic Discharge Nozzle
- Effective Suppression of Class A, B Fires
- Effective Suppression of Class C Fires
(Only Applicable To LPCB Approval Model)
- Suitable to Use on Live Electrical Equipment Up to 1000V
(Only Applicable To LPCB Approval Model)

Standards : Manufactured In Accordance With EN 3-7

Approvals : LPCB (UK), TUV (SG)

Origin : Made in Singapore



Ordering Matrix :

Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20801018	13A, 55B	A, B, C	BS EN 3-7:2004+A1:2007	LPCB
20801000	13A, 55B	A, B	SS EN 3-7 : 2012	TUV



GOOD QUALITY GREAT SERVICES

www.lingjack.com

LEW-MDS-C2ASE Rev02 (May26)
Specification subjects to change without prior notice