



# LINGJACK

## 林傑

### 3KG ABC STORED PRESSURE FIRE EXTINGUISHER

MODEL : C-3ASE

#### Specification :

- Capacity : 3 kg
- Extinguishing Medium : 40% ABC Dry Chemical Powder
- Propellant Type : Nitrogen
- Discharge Time : 11 sec
- Discharge Range : 3 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Size : Dia. 115 x 460(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 5.0 kg

#### Features :

- Outdoor UV Resistance Polyester Powder Coated
- Durable Plastic Discharge Nozzle
- Effective Suppression of Class A, B Fires
- Effective Suppression of Class C Fires  
(Only Applicable To LPCB Approval Model)
- Suitable to Use on Live Electrical Equipment Up to 1000V  
(Only Applicable To LPCB Approval Model)

**Standards :** Manufactured In Accordance With EN 3-7

**Approvals :** LPCB (UK), TUV (SG)

**Origin :** Made in Singapore

Ordering Matrix :

| Com No.  | Fire Rating | For Class Of Fire | Standard               | Approval |
|----------|-------------|-------------------|------------------------|----------|
| 20801220 | 13A, 55B    | A, B, C           | BS EN 3-7:2004+A1:2007 | LPCB     |
| 20801200 | 13A, 55B    | A, B              | SS EN 3-7 : 2012       | TUV      |



EN3-7:2004 + A1:2007  
Cert No. 501a



**GOOD QUALITY GREAT SERVICES**

[www.lingjack.com](http://www.lingjack.com)

LEW-MDS-C3ASE Rev01 (May26)  
Specification subjects to change without prior notice