



LINGJACK

林傑

9KG PURPLE K STORED PRESSURE FIRE EXTINGUISHER

MODEL : C-9PKSE

Specification :

- Capacity : 9 kg
- Extinguishing Medium : Purple K BC Dry Chemical Powder
- Propellant Type : Nitrogen
- Discharge Time : 17 sec
- Discharge Range : 7 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 530 mm
- Size : Dia. 181 x 600(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 13.2 kg

Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Effective Suppression of Class B Fires
- Effective Suppression of Class C Fires
(Only Applicable To LPCB Approval Model)
- Suitable to Use on Live Electrical Equipment Up to 1000V
(Only Applicable To LPCB Approval Model)

Standards : Manufactured In Accordance With EN 3-7

Approvals : LPCB (UK), TUV (SG)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20804502	233B	B, C	BS EN 3-7:2004+A1:2007	LPCB
2080450200001	233B	B	SS EN 3-7 : 2012	TUV



EN3-7:2004 + A1:2007
Cert No. 501a



TUV SÜD PSB

GOOD QUALITY GREAT SERVICES

www.lingjack.com

LEW-MDS-C9PKSE Rev01 (May26)
Specification subjects to change without prior notice