



Parts List				
Item	Description	Specification	Com No.	Qty.
1	Pressure Gauge	Working Temperature Range : 5 deg C To 60 deg C	03000300	1
2	Hook Bracket	Material : Mild Steel, Min 1.5mm Thick Finishing : Chrome Plated	03021700	1
3	Silkscreen Label	NA	NA	1
4	Valve Assembly	Refer To Technical Drawing 06E20 (03013100)	03013103	1
5	Medium	15% Water Additive	03011202	1
6	Medium	1% Foam Additive	03011201	1
7	Syphon Tube	Material : UPVC Plastic	03032900	1
8	Empty Cylinder	Material : JISG3141 Cold Roll Sheet, 1.5mm Thick Finishing : Red Epoxy Powder Coated	03098200	1
9	Hose And Foam Nozzle	Material (Hose) : Black Braided PVC Material (Nozzle) : Black PP Plastic	03006801	1
10	Water Filter	Material : HDPE Plastic	03033100	1
11	Plastic Skirt Dia.181	Material : UPVC Plastic	03065800	1
12	Body Belt	Material : UPVC Plastic	03002800	1

Technical Specification	
Description	Specification
Working Temperature	5 deg C To 60 deg C
Working Pressure	14 Bar
Test Pressure, PT	27 Bar @ 30 Sec
Maximum Allowable Pressure, PS	18 Bar
Fire Rating	34A/233B
Gross Weight	13.3 Kg

Ordering Matrix			
Com No.	Brand	Approval	Remarks
20801736 00000	COMBAT	LPCB	BS EN3
20801702 00000	COMBAT	TUV	SS EN3

LINGJACK ENGINEERING WORKS PTE LTD
 NO.1 WOODLANDS TERRACE #03-01
 LINGJACK INDUSTRIAL BUILDING
 SINGAPORE 738471
 TEL:(65)6759 4163 FAX:(65)6758 7513
 E-MAIL:COMBAT@LINGJACK.COM
 WEBSITE:WWW.COMBAT.COM.SG

Customer : - Project : -
 Title : Foam Portable Fire Ext, Stored Pressure 9L (C-9FSE)
 Drawing No. : 20801736 Com. No. :
 This drawing contains proprietary information and should not be reproduced or use in any way without written permission from Lingjack Engineering Works Pte Ltd.
 Scale : NTS Sheet : 1/1
 3rd Angle Projection :

10.02.09	Approved Drawing	TanCP	Lucas	00	A
Date	Description	Drawn	Approved	GA Rev	Pro Rev