



Parts List				
Item	Description	Specification	Com No.	Qty.
1	Pressure Gauge	Working Temperature Range : 5 deg C To 60 deg C	03000300	1
2	Hook Bracket	Material : 1.5mm Mild Steel Finishing : Chrome Plated	03021700	1
3	Artwork	Silkscreen	NA	1
4	Valve Assembly	Model 06E20	03013103	1
5	Medium	15% Water Additives	03011202	1
6	Syphon Tube	Materials : UPVC Plastic	03032900	1
7	Empty Cylinder	Material : JISG3141 Cold Roll Sheet, 1.5mm Thick Finishing : Red Epoxy Powder Coated	03098200	1
8	Hose And Horn	Material (Hose) : Black Braided PVC Material (Nozzle) : Red PP Plastic	03002901	1
9	Water Filter	Material : UPVC Plastic	03033100	1
10	Plastic Skirt	Materials : UPVC Plastic	03065800	1

Technical Specification	
Description	Specification
Working Temperature	5 deg C To 60 deg C
Working Pressure	14 Bar
Maximum Allowable Pressure,PS	18 Bar
Test Pressure	27 Bar @ 30sec
Fire Rating	21A
Gross Weight	13.30 Kg

Ordering Matrix			
Com No.	Brand	Approval	Remarks
20801737 00000	COMBAT	LPCB	BS EN3
20804300 00000	COMBAT	TUV	SS EN3

<p><b>LINGJACK ENGINEERING WORKS PTE LTD</b> NO.1 WOODLANDS TERRACE #03-01 LINGJACK INDUSTRIAL BUILDING SINGAPORE 738471 TEL:(65)6759 4163 FAX:(65)6758 7513 E-MAIL:COMBAT@LINGJACK.COM WEBSITE:WWW.COMBAT.COM.SG</p>	Customer : -	Project : -							
	Title : Water Additives Portable Fire Ext, Stored Pressure 9L (C-9WSEA)								
	Drawing No. : 20801737	Com. No. :							
	This drawing contains proprietary information and should not be reproduced or use in any way without written permission from Lingjack Engineering Works Pte Ltd.		Scale : NTS	Sheet : 1/1	10.02.09	Approved Drawing	Tan CP	Lucas	00
		3rd Angle Projection :		Date	Description	Drawn	Approved	GA Rev	Pro Rev