



# LINGJACK

## 林傑

### 20KG CO2 STORED PRESSURE MOBILE FIRE EXTINGUISHER

MODEL : C-20C

#### Specification :

- Capacity : 20 kg
- Extinguishing Medium : CO2
- Propellant Type : CO2
- Discharge Time : 44 secs
- Discharge Range : 10 m
- Working Pressure : 60 bar @ 20°C
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 3/8" x 6 meters  
(Optional Up To 12 meter Upon Request)
- Wheel Size : Diameter 406mm x 50mm
- Size : 590 (L) x 640 (D) x 1470(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 90 kg



#### Features :

- Heavy Duty Hose
- Forged Brass Chrome Plated Operating Valve with In-Build Safety Relief
- Suitable to Use on Live Electrical Equipment Up to 1000V
- Suitable for Electrical Fire
- Solid Rubber Wheel for Easy Maneuverable


**Standards :** Manufactured In Accordance With BS EN 1866-1 : 2007

**Approvals :** LPCB (UK), TUV (SG), BUREAU VERITAS (BV)

**Origin :** Made in Singapore

Ordering Matrix :

| Com No.       | Fire Rating | Class Of Fire | Standard          | Approval |
|---------------|-------------|---------------|-------------------|----------|
| 20802329      | 89B         | B             | BS EN 1866-1:2007 | LPCB     |
| 2080232900001 | 89B         | B             | BS EN 1866-1:2007 | TUV      |
| 20805750      | 89B         | B             | BS EN 1866-1:2007 | BV (MED) |



**GOOD QUALITY GREAT SERVICES**

[www.lingjack.com](http://www.lingjack.com)

LEW-MDS-C20C Rev02 (June26)

Specification subjects to change without prior notice