



# LINGJACK

## 林傑

### 25KG PURPLE K STORED PRESSURE MOBILE FIRE EXTINGUISHER

**MODEL : C-25PTP**

#### Specification :

- Capacity : 25 kg
- Extinguishing Medium : Purple K
- Propellant Type : Nitrogen
- Discharge Time : 30 secs
- Discharge Range : 10 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 3/4" x 6 meters  
(Optional Up To 12 meter Upon Request)
- Wheel Size : Diameter 406mm x 50mm
- Size : 440 (L) x 400 (D) x 930(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 49 kg



#### Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Forged Brass Chrome Plated Operating Valve with In-Build Safety Relief
- Suitable to Use on Live Electrical Equipment Up to 1000V
- Suitable for Electrical Fire
- Solid Rubber Wheel for Easy Maneuverable

**Standards :** Manufactured In Accordance With BS EN 1866-1 : 2007

**Approvals :** LPCB (UK), TUV (SG)

**Origin :** Made in Singapore

Ordering Matrix :

| Com No.       | Fire Rating   | Class Of Fire | Standard          | Approval |
|---------------|---------------|---------------|-------------------|----------|
| 21804700      | IIB (275B), C | B, C          | BS EN 1866-1:2007 | LPCB     |
| 2180470000001 | IIB (275B)    | B             | BS EN 1866-1:2007 | TUV      |



**GOOD QUALITY GREAT SERVICES**

[www.lingjack.com](http://www.lingjack.com)

LEW-MDS-C25PTP Rev02 (June26)  
Specification subjects to change without prior notice