


PARTS LIST				
Item	Description	Material	Com No	Qty
1	SP Turn Valve	Brass HTCZ120317-1	03020004	1
2	23mm Pressure Gauge	-	03000200	1
3	Iron Safety Pin	Nickel Plated Iron	03018600	1
4	50KG Cylinder With 16in Wheel	JIS3131 Hot Roll Sheet 3.6mm Thick	03067206	1
5	Powder Controllable Discharge Gun	PVC	03079206	1
6	3/4" x 6M Hose Assembly	Rubber	03003303	1
7	Syphon Tube	PVC	03104900	2

Technical Specification	
Description	Specification
Extinguisher Medium	AFFF
Working Temperature	5 To 60DegC
Max. Allowable Pressure, PS	20 Bar
Operating Pressure	14 Bar
Discharge Time	100 Sec
Discharge Effective Range	10 m
Fire Rating	34A/II B (2x21B + 233B = 275B)
Gross Weight	89 kg

Ordering Matrix			
Com No.	Brand	Approval	Remarks
21805800 00000	COMBAT	LPCB	BS EN1866-1
21805800 00001	COMBAT	TUV	BS EN1866-1

 LINGJACK ENGINEERING WORKS PTE LTD NO.1 WOODLANDS TERRACE #03-01 LINGJACK INDUSTRIAL BUILDING SINGAPORE 738471 TEL:(65)6759 4163 FAX:(65)6758 7513 E-MAIL:COMBAT@LINGJACK.COM WEBSITE:WWW.COMBAT.COM.SG	Customer : -		Project : -									
	Title : 50L Trolley Fire Extinguisher (Foam), Stored Pressure (C-50FTP)											
	Drawing No. : 21805800		Com. No. :									
	This drawing contains proprietary information and should not be reproduced or use in any way without written permission from Lingjack Engineering Works Pte Ltd.		Scale : NTS	Sheet : 1/1								
			3rd Angle Projection : 	20.07.11		Production Drawing.						
				Date	Description							