LINGJACK 林傑

6TR WATER MIST STORED PRESSURE FIRE EXTINGUISHER

MODEL: C-6WMFA



Specification :

- Capacity : 6 Ltr
- Extinguishing Medium : Water with Inilam AX & AFFF mixture
- Propellant Type : Nitrogen
- Discharge Time: 42.7 sec
- Working Pressure : 15 bar
- Working Temperature : +5Deg C to +60Deg C
- Hose Length : 490 mm
- Size : Dia. 181 x 602(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 11.0kg

Features :

- Eco-Friendly
- Durable Discharge Nozzle
- Resistance to corrosion according to EN3-7
- Effective Suppression of Class A, B & F Fires

Standards : Manufactured in accordance with EN3-7

Approvals : TUV (SG), Singapore Green Labelling Scheme (SGLS)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	Brand	Standard	Approval
20809263	21A, 144B, 75F	COMBAT	SS EN 3-7 : 2012	TUV, SGLS
20809267	21A, 144B, 75F	COMBAT	BS EN 3-7 : 2012	TUV
2080926700001	21A, 144B, 75F	COMBAT	BS EN 3-7 : 2012	BV (MED)

TÜV SÜD PSB

Green Label Singapore

2690

Specification subjects to change without prior notice