



# LINGJACK

## 林傑

### 1KG ABC STORED PRESSURE FIRE EXTINGUISHER

**MODEL : C-1ASE**

#### Specification :

- Capacity : 1 kg
- Extinguishing Medium : 40% ABC Dry Chemical Powder
- Propellant Type : Nitrogen
- Discharge Time : 9.53 sec
- Discharge Range : 3 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Size : Dia. 85 x 320(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 2.0 kg



#### Features :

- Outdoor UV Resistance Polyester Powder Coated
- Durable Plastic Discharge Nozzle
- Effective Suppression of Class A,B Fires
- Effective Suppression of Class C Fires  
(Only Applicable To LPCB Approval Model)
- Suitable to Use on Live Electrical Equipment Up to 1000V  
(Only Applicable To LPCB Approval Model)

**Standards :** Manufactured In Accordance With EN 3-7

**Approvals :** LPCB (UK), SETSCO (SG)

**Origin :** Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20800809	5A, 55B	A, B, C	BS EN 3-7:2004+A1:2007	LPCB
20800800	5A, 55B	A, B	SS EN 3-7 : 2012	SETSCO



EN3-7:2004 + A1:2007  
Cert No. 501a



**GOOD QUALITY GREAT SERVICES**

[www.lingjack.com](http://www.lingjack.com)