



LINGJACK

林傑

1 1/4"x30m HIGH PRESSURE HOSEREEL

MODEL : HR-0280, HR-0281, HR-0288

Specification :

- Hose Size : 1 1/4 " x 30m
- Design Pressure : 20 bar
- Working Temperature : 5 Deg C to 55 Deg C
- Hydrostatic Test Pressure : 30 bar at 5 mins
- Nozzle : C18 Pistol Grip Brass Jet Spray Nozzle
- Flow Rate (Jet) : 212 lpm at Inlet 6 bar
- K-Factor : 86.71
- Distance (Jet) : 18m at Inlet 6 bar
- Overall Size : Dia.: 650 x 310 (±5) (Depth)
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 30 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated Hose Reel
- High Quality and Pressure Red Semi Rigid Fire Hose Approved to EN694 : 2014
- 3 Way Control Nozzle (Spray-Jet-Off)
- Gunmetal 180° Double Swing Waterway
- Flexible Mounting Position
- For Offshore Application
- Design Accordance to Norsok Requirement

Standards : Manufactured in accordance with EN 671-1 : 2012

Approvals : LPCB (UK), BUREAU VERITAS (BV)

Origin : Made in Singapore

Ordering Matrix :


Com No.	Model	Waterway Material	Drum Material	Approval
80801500	HR-0280	Gunmetal LG2	Electro Galvanized Plate	LPCB
8080150000001	HR-0280	Gunmetal LG2	Electro Galvanized Plate	BV (MED)
80801600	HR-0281	Gunmetal LG2	Stainless Steel Plate	LPCB
8080160000001	HR-0281	Gunmetal LG2	Stainless Steel Plate	BV (MED)
80801601	HR-0288	Titanium	Stainless Steel Plate	LPCB



EN 671 - 1: 2012
Cert No. 501b



BUREAU
VERITAS



2690

GOOD QUALITY GREAT SERVICES

www.lingjack.com