



# LINGJACK

## 林傑

### 100KG MONNEX CARTRIDGE OPERATED MOBILE FIRE EXTINGUISHER

**MODEL : C-100MTC**

**Specification :**

- Capacity : 100 kg
- Extinguishing Medium : Monnex
- Propellant Type : 3.5kg CO2
- Discharge Time : 136 secs
- Discharge Range : 10 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 3/4" x 6 meters  
(Optional Up To 12 meter Upon Request)
- Wheel Size : Diameter 406mm x 50mm
- Size : 660 (L) x 690 (D) x 1120(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 171 kg



**Features :**

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Forged Brass Chrome Plated Operating Valve with In-Build Safety Relief
- Suitable to Use on Live Electrical Equipment Up to 1000V
- Suitable for Electrical Fire
- Solid Rubber Wheel for Easy Maneuverable

**Standards :** Manufactured In Accordance With BS EN 1866-1 : 2007

**Approvals :** LPCB (UK), SETSCO (SG)

**Origin :** Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	Class Of Fire	Standard	Approval
21803800	IIIB (296B), C	B, C	BS EN 1866-1:2007	LPCB
2180380000001	IIIB (296B)	B	BS EN 1866-1:2007	SETSCO



**GOOD QUALITY GREAT SERVICES**

[www.lingjack.com](http://www.lingjack.com)

Specification subjects to change without prior notice (0821 R03)