



LINGJACK

林傑

12KG ABC CARTRIDGE OPERATED FIRE EXTINGUISHER

MODEL : C-12ACE

Specification :

- Capacity : 12 kg
- Extinguishing Medium : 40% ABC Dry Chemical Powder
- Propellant Type : 225 gram CO₂
- Discharge Time : 25.8 sec
- Discharge Range : 10 m
- Working Pressure : 19.7 bar
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 620 mm
- Size : Dia. 181 x 654(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 18.0 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Effective Suppression of Class A,B Fires
- Effective Suppression of Class C Fires
(Only Applicable To LPCB Approval Model)
- Suitable to Use on Live Electrical Equipment Up to 1000V
(Only Applicable To LPCB Approval Model)


Standards : Manufactured In Accordance With EN 3-7

Approvals : LPCB (UK), BUREAU VERITAS (BV)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20801649	55A, 233B	A, B, C	BS EN 3-7:2004+A1:2007	LPCB
208016490002	55A, 233B	A, B, C	BS EN 3-7:2004+A1:2007	BV (MED)



GOOD QUALITY GREAT SERVICES

www.lingjack.com