



LINGJACK

林傑

50KG PURPLE K STORED PRESSURE MOBILE FIRE EXTINGUISHER

MODEL : C-50PTP

Specification :

- Capacity : 50 kg
- Extinguishing Medium : Purple K
- Propellant Type : Nitrogen
- Discharge Time : 58 secs
- Discharge Range : 10 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 3/4" x 6 meters
(Optional Up To 12 meter Upon Request)
- Wheel Size : Diameter 406mm x 50mm
- Size : 530 (L) x 550 (D) x 995(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 90 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Forged Brass Chrome Plated Operating Valve with In-Build Safety Relief
- Suitable to Use on Live Electrical Equipment Up to 1000V
- Suitable for Electrical Fire
- Solid Rubber Wheel for Easy Maneuverable

Standards : Manufactured In Accordance With BS EN 1866-1 : 2007

Approvals : LPCB (UK), SETSCO (SG)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	Class Of Fire	Standard	Approval
21804800	IIB (275B), C	B, C	BS EN 1866-1:2007	LPCB
2180480000001	IIB (275B)	B	BS EN 1866-1:2007	SETSCO



GOOD QUALITY GREAT SERVICES

www.lingjack.com

Specification subjects to change without prior notice (0821 R03)