



LINGJACK

林傑

75KG PURPLE K CARTRIDGE OPERATED MOBILE FIRE EXTINGUISHER

MODEL : C-75PTC

Specification :

- Capacity : 75 kg
- Extinguishing Medium : Purple K
- Propellant Type : 3.0kg CO2
- Discharge Time : 110 secs
- Discharge Range : 10 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 3/4" x 6 meters
(Optional Up To 12 meter Upon Request)
- Wheel Size : Diameter 406mm x 50mm
- Size : 580 (L) x 600 (D) x 1180(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 137 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Forged Brass Chrome Plated Operating Valve with In-Build Safety Relief
- Suitable to Use on Live Electrical Equipment Up to 1000V
- Suitable for Electrical Fire
- Solid Rubber Wheel for Easy Maneuverable

Standards : Manufactured In Accordance With BS EN 1866-1 : 2007

Approvals : LPCB (UK), SETSCO (SG)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	Class Of Fire	Standard	Approval
21804400	IVB (317B), C	B, C	BS EN 1866-1:2007	LPCB
2180440000001	IVB (317B)	B	BS EN 1866-1:2007	SETSCO



BS EN 1866-1:2007
Cert No. 501g



GOOD QUALITY GREAT SERVICES

www.lingjack.com