



# LINGJACK 林傑

## 9KG ABC CARTRIDGE OPERATED FIRE EXTINGUISHER

### MODEL : C-9ACE

#### Specification :

- Capacity : 9 kg
- Extinguishing Medium : 40% ABC Dry Chemical Powder
- Propellant Type : 150 gram CO<sub>2</sub>
- Discharge Time : 19.4 sec
- Discharge Range : 7 m
- Working Pressure : 14.6 bar
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 530 mm
- Size : Dia. 181 x 575(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 13.5 kg



#### Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Effective Suppression of Class A,B Fires
- Effective Suppression of Class C Fires  
(Only Applicable To LPCB Approval Model)
- Suitable to Use on Live Electrical Equipment Up to 1000V  
(Only Applicable To LPCB Approval Model)

**Standards :** Manufactured In Accordance With EN 3-7

**Approvals :** LPCB (UK), BUREAU VERITAS (BV)

**Origin :** Made in Singapore

Ordering Matrix :


Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20801608	43A, 233B	A, B, C	BS EN 3-7:2004+A1:2007	LPCB
20801608000001	43A, 233B	A, B, C	BS EN 3-7:2004+A1:2007	BV (MED)



EN3-7:2004 + A1:2007  
Cert No. 501a



BUREAU  
VERITAS



2690

**GOOD QUALITY GREAT SERVICES**

[www.lingjack.com](http://www.lingjack.com)