



LINGJACK

林傑

50LTR FOAM CARTRIDGE OPERATED MOBILE FIRE EXTINGUISHER

MODEL : C-50FTC

Specification :

- Capacity : 50 ltr
- Extinguishing Medium : Foam
- Propellant Type : 1.0kg CO2
- Discharge Time : 75 secs
- Discharge Range : 10 m
- Working Temperature : +5Deg C to +60 Deg C
- Hose Length : 3/4" x 6 meters
(Optional Up To 12 meter Upon Request)
- Wheel Size : Diameter 406mm x 50mm
- Size : 530 (L) x 550 (D) x 994(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 95 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Forged Brass Chrome Plated Operating Valve with In-Build Safety Relief
- Solid Rubber Wheel for Easy Maneuverable


Standards : Manufactured In Accordance With BS EN 1866-1 : 2007

Approvals : LPCB (UK), SETSCO (SG), BUREAU VERITAS (BV)

Origin : Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	Class Of Fire	Standard	Approval
21805300	34A,IVB (317B)	A, B	BS EN 1866-1:2007	LPCB
2180530000001	34A,IVB (317B)	A, B	BS EN 1866-1:2007	SETSCO
2180530000002	34A,IVB (317B)	A, B	BS EN 1866-1:2007	BV (MED)



GOOD QUALITY GREAT SERVICES

www.lingjack.com