



LINGJACK

林傑

6TR WATER MIST STORED PRESSURE FIRE EXTINGUISHER

MODEL: C-6WMFA

Specification :

- Capacity : 6 Ltr
- Extinguishing Medium : Water with Additive
- Propellant Type : Nitrogen
- Discharge Time: 42.7 sec
- Working Pressure : 15 bar
- Working Temperature : +5Deg C to +60Deg C
- Hose Length : 490 mm
- Size : Dia. 181 x 602(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 11.0kg



Features :

- Eco-Friendly
- Durable Discharge Nozzle
- Resistance to corrosion according to EN3-7
- Effective Suppression of Class A, B & F Fires


Standards : Manufactured in accordance with EN3-7

Approvals : TUV (SG), Singapore Green Labelling Scheme (SGLS)

Origin : Made in Singapore

Ordering Matrix :

| Com No. | Fire Rating | Brand | Standard | Approval |
|---------------|----------------|--------|------------------|-----------|
| 20809263 | 21A, 144B, 75F | COMBAT | SS EN 3-7 : 2012 | TUV, SGLS |
| 20809267 | 21A, 144B, 75F | COMBAT | BS EN 3-7 : 2012 | TUV |
| 2080926700001 | 21A, 144B, 75F | COMBAT | BS EN 3-7 : 2012 | BV (MED) |



GOOD QUALITY GREAT SERVICES

www.lingjack.com

Specification subjects to change without prior notice (0721 R02)