



LINGJACK

林傑

9LTR FOAM CARTRIDGE OPERATED FIRE EXTINGUISHER

MODEL : C-9FCE

Specification :

- Capacity : 9 ltr
- Extinguishing Medium : Foam
- Propellant Type : 75 gram CO2
- Discharge Time : 35 sec
- Discharge Range : 7 m
- Working Pressure : 17.0bar
- Working Temperature : +5Deg C to +60 Deg C
- Hose Length : 530 mm
- Size : Dia. 181 x 624(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 13.5 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Effective Suppression of Class A & B Fires

Standards : Manufactured In Accordance With EN 3-7

Approvals : LPCB (UK)


Origin : Made in Singapore

Ordering Matrix :

| Com No. | Fire Rating | For Class Of Fire | Standard | Approval |
|---------------|-------------|-------------------|------------------------|----------|
| 20801708 | 34A, 233B | A, B | BS EN 3-7:2004+A1:2007 | LPCB |
| 2080170800002 | 34A, 233B | A, B | BS EN 3-7:2004+A1:2007 | BV (MED) |



EN3-7:2004 + A1:2007
Cert No. 501a



GOOD QUALITY GREAT SERVICES

www.lingjack.com

Specification subjects to change without prior notice (0721 R02)