



LINGJACK

林傑

9LTR WATER ADDITIVES CARTRIDGE OPERATED FIRE EXTINGUISHER

MODEL : C-9WCEA

Specification :

- Capacity : 9 ltr
- Extinguishing Medium : Water with Additives
- Propellant Type : 75 gram CO2
- Discharge Time : 71.3 sec
- Discharge Range : 7 m
- Working Pressure : 16.5 bar
- Working Temperature : +5Deg C to +60 Deg C
- Hose Length : 540 mm
- Size : Dia. 181 x 624(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 14.7 kg

Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Effective Suppression of Class A Fires

Standards : Manufactured In Accordance With EN 3-7

Approvals : LPCB (UK), BUREAU VERITAS (BV)

Origin : Made in Singapore



Ordering Matrix :


Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20801709	21A	A	BS EN 3-7:2004+A1:2007	LPCB
2080170900001	21A	A	BS EN 3-7:2004+A1:2007	BV (MED)



EN3-7:2004 + A1:2007
Cert No. 501a



BUREAU
VERITAS



2690

GOOD QUALITY GREAT SERVICES

www.lingjack.com

Specification subjects to change without prior notice (0721 R02)