



LINGJACK

林傑

2 ½” BIB NOSE LANDING VALVE

Specification :

- Inlet : 2 ½” PN16 Flange
(Optional Inlet Size And Type Upon Request)
- Outlet : 2 ½” BS336 Female Instantaneous
- Design Pressure : 15 bar
- Seat Test Pressure : 16.5 bar
- Body Test Pressure : 22.5 bar
- Friction Loss : 0.7 bar
- Flow Rate : 8.7 L/sec at 4.7 bar ± 3 %
- K-Factor : 240.78
- Finishing : Red
(Optional Yellow Color Upon Request)
- Cast/Ductile Iron Hand Wheel Size : Ø150mm x 15mm (Thk)
(Optional Material Upon Request)
- Body Material : Gunmetal LG2
- Accessories : Plastic Blank Cap with SS Chain
(Optional Material Upon Request)
- Gross Weight : Approximate 7.5 kg (Flange Type),
Approximate 5.5 kg (Screw Type)



Features :

- Low Maintenance
- Excellence Quality
- High Flow Rate

Standards : Manufactured in accordance with BS5041-1 : 1987

Approvals : LPCB (UK) , SETSCO (SG)

Origin : Made in Singapore

Ordering Matrix :

| Com No. | Inlet Connection | Color | Model | Approval |
|----------|-------------------------|-------|----------|----------|
| 03097603 | 2 ½” PN16 FF Flange | Red | LV-BNF25 | LPCB |
| 03097604 | 2 ½” ANSI#150 FF Flange | Red | LV-BNF25 | LPCB |
| 03161600 | 2 ½” BSP(M) Thread | Red | LV-BNS25 | LPCB |



GOOD QUALITY GREAT SERVICES

www.lingjack.com

LEW-MDS-BNLPLV Rev00 (Dec21)

Specification subjects to change without prior notice