



# LINGJACK

## 林傑

### 2 ½" HORIZONTAL LANDING VALVE

#### Specification :

- Inlet : 2 ½" PN16 Flange  
(Optional Inlet Size And Type Upon Request)
- Outlet : 2 ½" BS336 Female Instantaneous
- Design Pressure : 15 bar
- Seat Test Pressure : 16.5 bar
- Body Test Pressure : 22.5 bar
- Friction Loss : 0.7 bar
- Flow Rate : 8.8 L/sec at 4.7 bar ± 3 %
- K-Factor : 243.55
- Finishing : Red  
(Optional Yellow Color Upon Request)
- Cast/Ductile Iron Hand Wheel Size : Ø150mm x 15mm (Thk)  
(Optional Material Upon Request)
- Body Material : Gunmetal LG2
- Accessories : Plastic Blank Cap with SS Chain  
(Optional Material Upon Request)
- Gross Weight : Approximate 7.5 kg (Flange Type),  
Approximate 5.5 kg (Screw Type)



#### Features :

- Low Maintenance
- Excellence Quality
- High Flow Rate

**Standards :** Manufactured in accordance with BS5041-1 : 1987

**Approvals :** LPCB ( UK ) , SETSCO ( SG )

**Origin :** Made in Singapore

Ordering Matrix :

Com No.	Inlet Connection	Color	Model	Approval
03034204	2 ½" PN16 FF Flange	Red	LV-HF25	LPCB
03036302	2 ½" BSPT(M) Thread	Red	LV-HS25	LPCB



**GOOD QUALITY GREAT SERVICES**

[www.lingjack.com](http://www.lingjack.com)

LEW-MDS-HLPLV Rev00 (Dec21)

Specification subjects to change without prior notice